



UNIQUE

Safety • Isolation
Fireproof • Acoustics
Environmental protection

Fireproof Ceiling

Characteristics

— High-quality Fireproof Ceiling Materials —

Made with a balanced combination of properly mixed and folded cellulose, cement and silicon sand.

Cast with high- pressure steam and then printed with elaborate patterns on the surface.

Toxin-free, fireproof, moisture-proof, sound-proof, aesthetic, non-asbestos, non-deformable, mold-free, easy to cut.

Suitable for wall ceiling of the suspension system.



Technical data




Thickness	3.5 mm
Specific Weight	1.3kgs/m ³
Flammability	Certified by CNS 14705 -first class flammability
Bending tolerance	17kgf/cm ²
Length change after water absorption	Below 0.20%

Specification	603x603(mm)
Packaging	9 pieces/ carton

Color and embossing

We can work with embossing and printing patterns that the customers demand.



N01



N02



N03




N04



011



021



11E



71E




91E




72E



01C



11C



71C

Relief series

Painting series

UNIQUE PLASTICS CORPORATION

P.O. BOX 108-258 TAIPEI TAIWAN

TEL: (886-2) 2741-5391

FAX: (886-2) 2776-9998 & 2772-0866

e.mail: uniquepc@ms14.hinet.net

<http://uniqueplastics.com>